

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



10/542485



(43) International Publication Date
5 August 2004 (05.08.2004)

PCT

(10) International Publication Number
WO 2004/065078 A1

(51) International Patent Classification⁷: B26B 19/14,
19/28

(21) International Application Number:
PCT/IB2004/050001

(22) International Filing Date: 12 January 2004 (12.01.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
03100098.7 20 January 2003 (20.01.2003) EP

(71) Applicant (for all designated States except US): KONIN-
KLJKE PHILIPS ELECTRONICS N.V. [NL/NL];
Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and

(75) Inventors/Applicants (for US only): BARON, Sint


[NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA Eind-
hoven (NL). KLOKMAN, Pieter, H. [NL/NL]; c/o Prof.
Holstlaan 6, NL-5656 AA Eindhoven (NL). KALMA,
Bauke [NL/NL]; c/o Prof. Holstlaan 6, NL-5656 AA
Eindhoven (NL). WESTRA, Thewis, M. [NL/NL]; c/o
Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).

(74) Agent: BOS, Kornelis, S.; Prof. Holstlaan 6, NL-5656
AA Eindhoven (NL).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

[Continued on next page]

(54) Title: SHAVING APPARATUS



(57) Abstract: A shaving apparatus has plurality of shaving heads, each with a rotatable cutting member (5) associated with and rotatable relative to a shear plate (3). For driving the cutting members (5), a plurality of drive units (9) is provided, each of said units extending at least from drive rim (7) engaged for driving the drive unit to a coupling end (27) coupled to one of the cutting members (5) for transmitting a rotation of the drive unit (9) to the cutting member (5). The drive rims (7) of the drive units (9) are suspended for rotation about axes of rotation (20) that are oriented at angles relative to each other and diverge from each other in a direction from the drive rim (7) to the coupling (27).

WO 2004/065078 A1



(84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM,

PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Shaving apparatus

This invention relates to a shaving apparatus comprising:

a plurality of shaving heads, each comprising a circular shear plate provided with hair-entry apertures;

5 a rotatable cutting member associated with and rotatable relative to the shear plate,

a motor, and

a drive structure coupling said motor to said cutting members for driving the cutting members into rotation, said drive structure comprising a plurality of drive units, each of said drive units extending at least from a drive rim engaged for driving the drive unit to a coupling end coupled to one of said cutting members for transferring rotation of the drive

10 unit to the cutting member,
wherein at least the drive rims of the drive units are each suspended for rotation about an axis of rotation.

15

Such a shaving apparatus is known from U.S. Pat. No. 4,257,161. According to this document, a shaving apparatus has a floating shaving head comprising a shear plate with hair-entry apertures, a cutting member which is rotatable relative to the shear plate, and a tiltable rotatable coupling spindle which is rotationally coupled at one end to the cutting

20

member and at the other end to a drive mechanism. At at least one end of the coupling spindle, the coupling is a three-point coupling. In one embodiment, the cutting member has three coupling openings which are distributed around the rotational axis of the cutting member, and the coupling spindle is provided with three axially extending coupling members which engage in the respective coupling openings.

25

The coupling spindle may be provided with a flange which is housed in a cavity in a hub of a gear wheel of the drive mechanism. The flange is movable in the cavity to permit a tilting and axial displacement of the coupling spindle, and three ribs may be formed on the wall of the cavity for respective engagement in three recesses in the periphery of the flange to form a three-point coupling at the other end of the coupling spindle. The ribs

are distributed over and extend parallel to the rotational axis of the gear wheel, and the recesses are correspondingly distributed over the rotational axis of the coupling spindle. Such an apparatus allows the axes of rotation of the (usually toothed) drive rims to be offset and preferably closer together than the axes of rotation of the cutting members, so that a compact transmission is obtained. One reason why a compact transmission is advantageous is that it allows the housing to taper from a relatively large shear plate holder to the motor that has a cross-section that is substantially smaller than the surface of the shear-plate holder. However, the coupling spindles that are tiltable relative to the drive rims are oriented at a relatively large angle to each other, to the drive rims, and to the shaving heads. This entails that a specific design of the couplings is required to prevent a limitation of the freedom of tilting of the shaving heads, and to prevent that relatively much friction and wear occurs at the couplings and where the spindles are coupled to the drive rims, even if the difference between the spacing between the axes of rotation of the drive rims and the spacing between the axes of rotation of the cutting members is relatively small. A further consequence is that, on pivoting or mounting of the shear-plate holder into its operating position, the coupling ends of the coupling spindles are out of line with the coupling openings of the cutting members and need to be urged into alignment with the coupling openings against a spring force before engagement with the coupling openings of the cutting members.

U.S. Pat. No. 3,890,705 discloses an apparatus that has a coupling pin at the end of the coupling spindle, which pin engages with a coupling slot in the cutting member with a large amount of play. This allows the cutting member to move back and forth relative to the coupling spindle in the longitudinal direction of the slot, which may cause wear and unpleasant noise.

It is an object of the invention to provide a solution that allows the distance between the centers of the drive rims of the drive units coupled to each of the cutting members to be substantially smaller than the distance between the centers of the cutting members, while at least reducing friction, wear, noise, and tilt obstruction normally associated with prior art apparatuses having tiltable spindles, so as to overcome the offset between, on the one hand, the distances between the centers of the drive rims and, on the other hand, the distances between the centers of the cutting members.

According to the present invention, this object is achieved by providing an apparatus according to claim 1. The mutually diverging orientations of the axes of rotation of

the drive rims allow the centers of the cutting members to be spaced apart further than the centers of the drive rims, without requiring the rotatable spindle of each drive unit to extend at an angle relative to the drive rim coupled thereto.

Particular embodiments of the invention are set forth in the dependent claims.

5 Further aspects, effects and details of the invention are described with reference to an example shown in the accompanying drawings.

Fig. 1 is a somewhat schematical front elevation of a shaving apparatus
10 according to an embodiment of the invention having three floating heads,

Fig. 2 is a somewhat schematical side elevation of the shaving apparatus of Fig. 1, with one of the shaving heads shown in cross-section taken on the line II-II in Fig. 1,

Fig. 3 is a cut-away perspective view of the motor and the drive structure of the apparatus according to Figs. 1 and 2,

15 Fig. 4 shows a schematical longitudinal section taken along the axes of rotation of a central gear wheel and the drive rim of one of the drive units, and

Fig. 5 is a somewhat schematical side elevation of a shaving apparatus according to another embodiment of the invention with two of the shaving heads shown in cross-section along respective center lines.

20

The shaving apparatus shown in Figs. 1 and 2 comprises a housing 1 on which is mounted a shear-plate holder 2 for three shear plates 3. The shear plates 3 have hair entry apertures 4. A rotary cutting member 5 is situated on the inner side of each shear plate 3, for
25 cooperation therewith in known manner.

The cutting members are rotated relative to the respective shear plates by a drive structure comprising an electric motor 10 and a transmission, to which the cutting members 5 are each coupled. The cutting members 5 are each coupled to an associated coupling spindle 6. In their turn, the spindles are each coupled to a drive rim 7. According to
30 the present example, the drive rim is a toothed rim engaged by a gear wheel, but in principle the drive rim may also be designed to be engaged in other manners, such as by friction, by a pulley, by a belt, or by a drive chain. A central gear wheel 8 is journaled centrally between the toothed rims 7, and an upper, outwardly facing gear engages each of the toothed rims. A pinion 15 fixed on the motor shaft 16 engages an inwardly facing gear of the gear wheel 8.

The toothed rims 7 and an associated shaft 11 are each rotatably journaled in a mounting plate 12.

To each shaft 11, a hub 13 is connected of which click fingers 22 each extend into an associated one of the spindles 6 and engage an inwardly facing rim 17 to keep the hubs 13 and the associated spindles 6 together when the shear plate holder 2 is dismounted. A compression coil spring 23 is mounted inside a cavity 14 formed by axial bores in the spindle 6 and in the hub 13, which coil presses the coupling end 27 of the spindle 6 into engagement with the cutting member 5 or at least with a coupling member for driving the cutting member. The coil spring 23 exerts a force on the spindle 6 in the direction of the associated cutting member 5. This force is transmitted to the cutting member 5 by the coupling spindle 6 and via the cutting member 5 to the associated shear plate 3, the flanged edge 19 of which is thereby pressed against the shear-plate holder 2. In use, the shear plates 3, together with the associated cutting members 5 and coupling spindles 6, can be pressed inwards against the action of the springs 23, under the pressure of which the shear plates are held against the user's skin.

All three cutting members 5, are coupled to the drive motor 10 in the above manner, the three toothed rims 7 nesting with the single centrally disposed gear wheel 8.

Ribs or grooves are formed on the wall of the cavity in each spindle and cooperate with ribs or grooves on the hub 13. Thus, a multi-point coupling (preferably having three or more point, line and/or surface contacts) is obtained between the hub 13 and the spindle 6 to transmit the rotary movement of the toothed rim 7 to the coupling end 27 of the spindle 6. The spindle 6 may be tilted relative to the toothed rim to accommodate to the position of the center of the cutting member 5 relative to the axis of rotation 20 of the toothed rim 7, for instance to assume a position that is slightly angled relative to the axis of rotation 20 of the toothed rim 7.

The coupling end 27 of each coupling spindle 6 remote from the hub 13 is triangular and bears on a wall of a correspondingly shaped recess 21 in the cutting member 5. The spindle 6 is thus also coupled to the cutting member 5 by a multi-point coupling, which will permit a tilting movement of the coupling spindle and the cutting member relative to each other.

The axes of rotation 20 of the drive rims 7 are oriented at angles relative to each other and diverge from each other in a direction from the drive rim 7 to the coupling end 27. This allows the centers of the toothed rims 7 to be closer together than the centers of the cutting members 5 and hence provides a more compact and lightweight construction with

smaller drive wheels, without entailing the disadvantage of a relatively large angle between the spindle 6 and the cutting member 5 or the disadvantage of a substantial angle between the spindle 6 and the hub 13. This, in turn, reduces friction and wear in the transmission. The relatively small angle between the spindle 6 (or more generally, the drive unit) and the center line of the shaving head in its neutral position provides the advantage that the maximum angle between the cutting member 5 and the spindle 6 that can occur when the floating shaving head is tilted through a given angle from its neutral position, by pressing it inwards on one side, is reduced. Accordingly, the maximum angle through which the shaving heads are capable of tilting from their neutral positions is increased.

That the shaving heads can be tilted through a wider angle is especially useful for shaving apparatuses of which the shear-plate holder consists of a number of elements, such as floes or panels, that are tiltable with respect to each other.

Fig. 5 shows an apparatus of which the axes of rotation of the drive rims for the different shaving heads are oriented at different angles relative to each other.

The mutually angled configuration of the axes of rotation of the drive rims can be applied with particular advantage to apparatuses comprising more than three shear plates, resulting in a relatively large shear-plate holder, which may be flat or contain portions that extend at substantial angles relative to each other.

The angle between the axes of rotation of the toothed rims is preferably at least 3° . In particular if a generally convex design of the shear-plate holder is desired, the angle between the axes can be quite large, for instance up to 20 or 45° . The preferred angle for a shaver with an average, customary shear-plate holder is about 8 to 10° .

To drive the cutting members 5 of all shaving heads uniformly, the axis of rotation of the central gear wheel 8 preferably extends centrally between the axes of rotation of the toothed rims 7 of the drive units 9 and at the same angle to each of the axes of rotation of the toothed rims 7.

CLAIMS:

1. A shaving apparatus comprising:
a plurality of shaving heads, each comprising a circular shear (3) plate provided with hair-entry apertures (4); a rotatable cutting member (5) associated with and rotatable relative to the shear plate (3),
5 a motor (10), and
a drive structure coupling said motor (10) to said cutting members (5) for driving the cutting members (5) into rotation, said drive structure comprising a plurality of drive units (9), each of said drive units extending at least from a drive rim (7) engaged for driving the drive unit to a coupling end (27) coupled to one of said cutting members (5) for
10 transferring rotation of the drive unit (9) to the cutting member (5),
wherein at least the drive rims (7) of the drive units (9) are each suspended for rotation about an axis of rotation (20),
characterized in that, the axes of rotation (20) of said drive rims (7) are oriented at angles relative to each other and diverge from each other in a direction from the drive rim (7) to the
15 coupling end (27).
2. An apparatus according to claim 1, in which the angle between said axes of rotation of said drive rims is at least 3°.
- 20 3. An apparatus according to claim 1 or 2, further comprising a central gear wheel (8) engaging said drive rims (7), said central gear wheel being rotatable about an axis of rotation extending between the axes of rotation of said drive rims (7) of said drive units (9).
- 25 4. An apparatus according to any one of the preceding claims, further comprising a shear-plate holder (2) comprising a number of elements, each holding at least one shear plate, which elements are tiltable with respect to each other.

5. An apparatus according to any one of the preceding claims, further comprising a shear-plate holder (2) comprising a number of elements, each holding at least one shear plate, which elements extend at angles to each other.

5 6. An apparatus according to any one of the preceding claims, in which at least two of said angles between axes of rotation (20) of said drive rims (7) are different from each other.

7. An apparatus according to any one of the preceding claims, in which the
10 number of shaving heads is larger than three.

1/5




Fig. 1

2/5




Fig. 2

4/5




Fig. 4

5/5




Fig. 5

INTERNATIONAL SEARCH REPORT

PCT/IB2004/050001

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 B26B19/14 B26B19/28

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
 IPC 7 B26B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 687 481 A (DE BOER JAN ET AL) 18 November 1997 (1997-11-18) column 10, line 57 -column 11, line 18; figures 1,2	
A	EP 0 378 266 A (PHILIPS NV) 18 July 1990 (1990-07-18) column 1, line 50 -column 2, line 48; figures 1,2	
A	US 4 257 161 A (BIJL HENDRIK A C ET AL) 24 March 1981 (1981-03-24) cited in the application column 2, line 6 - line 57; figures 1,2	
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

23 April 2004

Date of mailing of the international search report

14/05/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Maier, M

INTERNATIONAL SEARCH REPORT

IB2004/050001

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>US 4 001 932 A (HERRICK WALLACE D) 11 January 1977 (1977-01-11) column 2, line 4 -column 3, line 21; figures 1-3</p>	

INTERNATIONAL SEARCH REPORT

PCT/IB2004/050001

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5687481	A	18-11-1997	AT 169256 T	15-08-1998
			CA 2168572 A1	07-12-1995
			CN 1130366 A ,B	04-09-1996
			DE 69503873 D1	10-09-1998
			DE 69503873 T2	04-03-1999
			EP 0720523 A1	10-07-1996
			ES 2122594 T3	16-12-1998
			WO 9532843 A1	07-12-1995
			JP 9501090 T	04-02-1997
EP 0378266	A	18-07-1990	NL 8900071 A	01-08-1990
			AT 127063 T	15-09-1995
			CN 1044061 A	25-07-1990
			DE 69021898 D1	05-10-1995
			DE 69021898 T2	02-05-1996
			EP 0378266 A1	18-07-1990
			JP 2224785 A	06-09-1990
			US 5031315 A	16-07-1991
US 4257161	A	24-03-1981	NL 7713044 A	30-05-1979
			AT 362678 B	10-06-1981
			AT 842678 A	15-10-1980
			AU 520628 B2	11-02-1982
			AU 4185078 A	07-06-1979
			BR 7807780 A	31-07-1979
			CA 1102535 A1	09-06-1981
			CH 635022 A5	15-03-1983
			DE 2850802 A1	31-05-1979
			ES 475407 A1	01-04-1979
			FR 2409831 A1	22-06-1979
			GB 2008467 A ,B	06-06-1979
			GB 2057955 A ,B	08-04-1981
			HK 8283 A	03-03-1983
			HK 53483 A	18-11-1983
			IT 1100195 B	28-09-1985
			JP 1214827 C	27-06-1984
			JP 54081960 A	29-06-1979
			JP 58049273 B	02-11-1983
			MX 146107 A	14-05-1982
			NZ 189001 A	30-03-1982
			SE 424614 B	02-08-1982
			SE 7812097 A	29-05-1979
			SG 48682 G	25-02-1983
US 4001932	A	11-01-1977	US 4077120 A	07-03-1978
			AT 334781 B	10-02-1976
			AT 957073 A	15-05-1976
			AU 6159473 A	24-04-1975
			CA 975549 A1	07-10-1975
			CH 562671 A5	13-06-1975
			DE 2357373 A1	30-05-1974
			FR 2207444 A5	14-06-1974
			GB 1406139 A	17-09-1975
			JP 49082453 A	08-08-1974
			NL 7315500 A	21-05-1974
			AT 334780 B	10-02-1976
			AT 617773 A	15-05-1976
			BE 802113 A1	05-11-1973

INTERNATIONAL SEARCH REPORT

IB2004/050001

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4001932	A	CH 580477 A5	15-10-1976
		FR 2193345 A5	15-02-1974
		JP 49056761 A	01-06-1974
		LU 68009 A1	13-09-1973
		NL 7309787 A	16-01-1974
		US 3844033 A	29-10-1974